

## Peach Type Push Trolley



Capacity	Length	Width	Height	I-beam	Wheel Dia	Hole	Shaft	Plate
0.5T	176	180	183	60-128	72	28	20	6
1T	202	195	235	68-128	91	45	25	8
2T	230	215	255	74-128	103	48	30	10
3T	275	238	307	88-154	123	70	35	10
5T	302	285	345	100-178	142	71	40	14

## Trapezoidal Push Trolley



Capacity	Length	Width	Height	I-beam	Wheel Dia	Hole	Shaft	Plate
0.5T	195	180	170	50-108	81	28	20	6
1T	210	180	175	50-108	90	40	20	8
2T	240	220	186	58-140	107	40	22	10
3T	277	250	242	80-150	125	58	30	12
5T	370	265	315	100-140	168	67	32	14
10T	370	300	460	110-200	168	94	33	16

## Anti-collision Push Trolley



Capacity	Length	Width	Height	I-beam	Wheel Dia	Hole	Shaft	Plate
1T	193	262	216	50-170	75	30*35	30	8
2T	230	275	255	68-170	92	40*50	34	10
3T	278	292	285	88-170	115	40*50	40	12
5T	320	370	345	94-194	125	50*75	45	14
10T	385	410	435	88-225	157	75*100	58	20

## Anti-collision Pull Trolley



Capacity	Length	Width	Height	I-beam	Wheel Dia	Hole	Shaft	Plate
1T	202	260	235	68-128	91	45	25	8
2T	230	280	255	74-128	103	48	30	10
3T	275	300	307	88-154	123	70	35	10
5T	302	335	345	100-178	142	71	40	14

## Trapezoidal Pull Trolley



Capacity	Length	Width	Height	I-beam	Wheel Dia	Hole	Shaft	Plate
1T	210	225	201	50-108	90	40	20	8
2T	240	270	202	58-140	107	40	22	10
3T	277	290	250	80-150	125	58	30	12
5T	370	275	315	100-140	168	67	32	14
10T	370	300	460	110-200	168	94	33	16

## Anti-collision Pull Trolley



Capacity	Length	Width	Height	I-beam	Wheel Dia	Hole	Shaft	Plate
1T	193	322	216	50-170	75	30*35	30	8
2T	230	335	255	68-170	92	40*50	34	10
3T	278	352	285	88-170	115	40*50	40	12
5T	320	320	345	94-194	125	50*75	45	14
10T	385	475	435	88-225	157	75*100	58	20